

Applications

- » Also suitable for high-alloy steel
- » Low to medium levels of smoke and dust
- » Occasional to frequent use

Properties

- » Automatic Start/Stop (optional)
- » Exhaust arm up to 4 m
- » Rotating exhaust hood

Benefits

- » Safe operation by rotation field control
- » Maintenance door allows easy filter change
- » Exhaust arm requires less adjustment due to exhaust hood design
- » Increased safety due to filter monitoring

Accessories

- » Automatic Start/Stop

ProfiMaster

- » Robust quality
- » High capacity filter



Order Data

Art. No.	Description
60 650 100	2 m Arm, flexible exhaust arm
60 650 101	3 m Arm, flexible exhaust arm
60 650 102	4 m Arm, flexible exhaust arm
60 650 103	2 m Arm, rigid metal tube arm
60 650 104	3 m Arm, rigid metal tube arm
60 650 105	4 m Arm, rigid metal tube arm
109 0033	Pre-filter mats (10 per set)
109 0457	Main filter 17 m ²

Technical Data

Filter	
Filter stages	2
Filter method	Disposable filter
Filter surface	ca. 17 m ²
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filter efficiency	> 99.5 %
Filterclass	E12
Additional filters	Pre-filter
Basic data	
Extraction capacity	1,100 m ³ /h
Dimensions (w x d x h)	785 x 730 x 950 mm
Weight	105 kg
Motor power	1.1 kW
Power supply	3 x 400 V / 50 Hz
Rated current	2.3 A
Noise level	70 dB(A)
Additional information	
IFA-Certification	W3-Approved
Fan type	Radial fan

