

Filter-Cell XL - Art. No.:60 200

- » Compact
- » Automatic filter cleaning



Applications

- » High levels of smoke and dust
- » Non-stop operation
- » For exhaust hoods, extraction tables and robot cells

Benefits

- » High efficiency due to automatic filter cleaning
- » Space-saving due to compact design
- » Easy installation since unit is delivered ready to plug in ("plug and play")
- » Best health protection for employees by use of KemTex® ePTFE filter cartridge with surface filtration
- » Safe operation by rotation field control

Properties

- » 160mm duct connection
- » Automatic filter cleaning
- » KemTex® ePTFE filter cartridge
- » Height-adjustable feet
- » Rotation field control

Variants

- » Other voltages

Technical Data

Art. No	60 200
Filter	
Filter method	Cleanable filter
Filter cleaning method	Rotating nozzle
Filter surface	ca. 10 m ²
Type of filter	Filter cartridge
Filter material	ePTFE-membrane
Filter efficiency	> 99.9 %
Dust classification	M
Basic data	
Extraction capacity	1,000 m ³ /h
Dimensions (w x d x h)	655 x 655 x 1,460 mm
Weight	155 kg
Motor power	1,5 kW
Power supply	3 x 400 V / 50 Hz
Noise level	69 dB(A)
Additional information	
Fan type	Radial fan



Suitable for alveole exchangeable dusts
separation > 99 % of particles < 0,4 µm